

Instaglaze

UHS, high solids, wet-look sealer finish



Instaglaze is a floor polish designed to be used in conjunction with ultra-high speed burnishing equipment. Instaglaze is easy to apply and is very quickly restored to a brilliant shine without any need for a spray buff. Instaglaze will provide an outstanding finish using propane, battery, petrol

or electric burnishing machinery.

Instaglaze is a unique advancement in floor polish technology that is designed for use in high traffic areas that require consistent high gloss and safety underfoot.

BENEFITS

- Brilliant Wet-Look Gloss – When buffed or burnished correctly, Instaglaze produces an unmatched, deep-gloss which is durable and very scratch resistant.
- Excellent Reparability – Instaglaze responds exceptionally well to cleaning and buffing programs. It is quickly and easily revived to a deep shine when buffed or burnished with electric buffing or burnishing machines.
- Coating Performance – Provides optimal durability and resistance to traffic marks, black heel marks and scuffing.
- Slip Resistance – Instaglaze provides exceptional slip resistance.

Recommended applications:

Ideal for use on vinyl, slate, terrazzo, terracotta marble and granite. On stone surfaces and on polished concrete it is recommended that a base coat of Instaseal be applied first. Instaglaze is ideally suited to floors in commercial and retail environments.

HOW TO USE

Read and understand the MSDS before use
Always pre-test in an inconspicuous location for sensitivity to chemicals.

Preparation:

Strip off old polish and wax residues using floor coatings remover. Ensure that the floor is thoroughly rinsed with clean water and is totally dry.

Considerations:

Slip resistance: Instaglaze provides conformance with AS/NZS 4586:2004 slip resistance classification of new pedestrian surface materials (wet and dry).

PRODUCT SPECIFICATIONS

Product code: AP425

pH: 7.5

Colour: N/A

Safety: Non hazardous

Packaging: 500ml, 5lt & 15lt.



Instaglaze

UHS, high solids, wet-look sealer finish

HOW TO USE

Read and understand the MSDS before use
Always pre-test in an inconspicuous location for sensitivity to chemicals.

Preparation:

Strip off old polish and wax residues using floor coatings remover. Ensure that the floor is thoroughly rinsed with clean water and is totally dry.

Application:

Apply 3 to 5 coats of Instaglaze depending on the porosity of the surface and the expected amount of traffic. Repeated thin, evenly spread coats are better than one heavy application.

If Instaseal has been applied as a base coat, only 2 to 3 coats of Instaglaze need to be applied. Instagloss can be applied as soon as the Instaseal is touch dry.

Coverage is 50-80m² per litre per coat depending on the porosity of the surface.

Directions:

1. Apply Instaglaze using a clean polish applicator. Spread a thin coat over the floor area using slightly overlapping strokes.
2. Allow to dry (30-40 minutes).
3. Apply the second and subsequent coats in the same manner as the first. Apply each coat at right angles to the previous coat to ensure even coverage.
4. Allow at least 12 hours before returning the floor to normal use.

Maintenance:

Maintain the Instaglaze floor finish using ProNeutro neutral cleaner. Buff regularly using Instabuff or Instabuff Super and a white, grey or red pad. Use an electric or battery powered polishing machine capable of between 150 and 1000rpm.

See article on how to apply polish.

