

Solv Strip

Premium radical strength floor coatings stripper

Solv Strip is a new generation floor coatings stripper that is guaranteed to work quickly and effectively saving you time and money. Solv Strip is possibly the most advanced solvent based floor coatings stripper on the market today. Solv Strip is designed to tackle tough solvent sealers and polish build-ups on resilient flooring such as terracotta, terrazzo and concrete. This truly is a remarkable achievement in coatings removal technology.

BENEFITS

- Power-packed – Serious stripping action on solvent based coatings, burnish build-ups and semi-permanent sealers.
- Fast action – begins to liquefy coating immediately on contact with the surface.
- Labour saving – Minimal scrubbing is required ensuring that time and labour is minimized.
- Free rinsing – Exceptionally easy to rinse slurry and residues.

PRODUCT SPECIFICATIONS

Product code: AP406



Recommended applications:

Solv Strip is safe for use on most resilient floors and quickly softens and emulsifies old worn and discoloured finishes for easy removal. Solv Strip is ideal for removing solvent sealers, base sealers and polish build-ups from natural stone, concrete and terrazzo. Do not use on wood, vinyl, linoleum and plastic flooring.

HOW TO USE

Read and understand the MSDS before use
Always pre-test in an inconspicuous location.

*****Do not use on vinyl and linoleum floors*****

Directions:

1. Sweep area thoroughly to remove any soiling that could damage the floor if caught under scrubbing equipment
2. Apply solution liberally to floor area with a cotton mop ensuring that the area is thoroughly wet. (Always work in small controllable area sizes)
3. Allow at least 5 minutes dwell time and then agitate with low speed rotary scrubber or auto-scrubber fitted with a black, brown or high productivity pad.
4. Be careful to ensure that the area does not "dry out" on the surface.
5. After scrubbing, pick up slurry and rinse thoroughly with clean water to ensure that all stripper and sealer residues are removed.
6. Allow floor to dry before with the restoration process and re-strip any areas that may still have polish build-up or that were missed in the first application.