

Defender CSD Pure

Stone consolidator and strengthener

Defender CSD Pure is a proprietary impregnating sealer which consolidates friable material and strengthens the substrate. Although suited to a wide range of materials it is most popular with construction materials such as sandstone, limestone, clay and concrete. It reacts with the substrate material creating an extremely strong and durable bond which protects the substrate from structural weakening and erosion for many, many years.

Certification:

Test report: Resistance to salt attack AS/NZS 4456.10-2003

Benefits

- Consolidates – Defender CSD Pure consolidates friable and loose materials within the stone.
- Substrate Strengthening – Defender CSD Pure dramatically increases the strength of the substrate which in turn dramatically improves durability and longevity.
- Limestone Protection – Provides unparalleled strengthening to Limestone where many sealers fail.
- Deep Penetration – Defender CSD Pure is based on an extremely small molecule size which enables it to penetrate to between 10 and 20mm in porous substrates.
- Long Term Benefits - Defender CSD Pure's long lasting consolidating and strengthening protects sandstone, limestone, engineered concrete and porous construction materials from deterioration and spalling.
- UV Stable – Ideally suited for both indoor and outdoor use.
- Vapour permeable – won't trap moisture. Does not hinder the natural passage of water vapour.

Benefits continued

- Retains Newness – the high performance protection and long life span offered by Defender CSD Pure is ideal for the preservation and preventative maintenance of: Heritage buildings, monuments, sandstone & limestone structures, construction concrete such as bridges, marine and port structures, concrete and clay paved walkways, parking areas, stone building facades and perimeter walling, pool surrounds and patios.
- Natural Look – will not discolour or alter the natural look of recommended substrates.

Recommended applications:

Formulated to provide premium protection to porous construction materials and is ideally suited to the protection of heritage and delicate/friable/crumbling stone. Defender CSD is ideal for limestone, sandstone and concrete structures.

PRODUCT SPECIFICATIONS

Product code: AP675

pH: 7.5

Colour: N/A

Safety: Non hazardous

Packaging: 500ml, 5lt & 15lt.



Defender CSD Pure

Stone consolidator and strengthener

Considerations:

Not to be used as a sub-terrain waterproofing. Should not be applied if temperature is above 40 degrees or if rain is expected within 2 hours of application. If rain has preceded the application, the surface should be allowed 24 hours to dry completely.

Expected Wear:

Defender CSD Pure will provide premium protection for up to 15 years and in many applications, several years longer. However application methods, weather conditions, traffic, harsh cleaning methods and substrate type will affect wear. Avoid use of solvents, strong acids and strong alkalis for extended sealer life. It is recommended that the sealer be re-applied every 8 - 12 years where harsh conditions exist.

Surface Preparation:

- New installations must be fully cured before application of Defender CSD Pure (Min 48 hours, however some concrete installations may take up to 7 days to cure. Confirm with the structural engineer).
- Existing stone and grout must be totally clean, dry and chemical free.
- Coverage can vary dramatically depending on the degree of porosity, but is normally 5 to 15 m² / Lt per coat for open structure, highly porous substrates and 15 to 25 m² / Lt per coat for dense, less porous substrates.
- Do not apply in direct sunlight. Temperature must be between 10°C and 28°C.
- Highly absorbent surfaces may require two coats.

Adhesive Compatibility:

When a tile is dip sealed prior to being installed, it will become highly water repellent. This means that a standard water based adhesive may not adhere to the surface. A suitable polymer modified grout should be used, which is designed to overcome the repellency of a penetrating sealer.

Compatible adhesives include:

1. Davco SE-7 (with Davelastic)
2. Mapie Granirapid

Application:

- Apply 1 to 2 coats of Defender CSD Pure by generously saturating the surface using a polish applicator, roller or sprayer to an area which can be easily reached. (Approximately 15m²). Ensure even coverage. When treating vertical surfaces, start application from the bottom, moving upwards to avoid uneven coverage.
- The surface must be shiny wet with a liquid film for at least 30 seconds. For very porous substrates more sealer may need to be applied.
- Allow 5 - 10 minutes for the sealer to absorb into the surface. On horizontal surfaces move the excess product with a squeegee to a new section.
- If a second coat is to be applied, wait 20 to 30 minutes and repeat the process.
- Using absorbent towelling or applicator, wipe off any sealer remaining on the surface after 10 minutes of the last application. Moisten the towel with Methylated Spirits to remove residues which have dried on the surface.
- Allow 6 - 12 hours before returning area to traffic. Keep dry for 24 hours. Achieves a full cure in 24-48 hours.

