

# Extracta Pro

## High temperature extraction powder



Extracta Pro is a premium quality extraction detergent liquid. This innovative emulsifier formulation has a well buffered pH, with a unique combination of solvents, detergents and water softeners for cutting through the toughest of soils, taking the "sweat" out of carpet cleaning. It is perfect for the hottest of truck mount cleaning systems and holds up to the ultra high heat therefore minimizing residual deposits and clogged spray jets.

### BENEFITS

- Premium Cleaning Action** – Got the muscle to cut through stubborn oily soils. Emulsifies tracked-in particulate soiling, releasing it for efficient extraction.
- High Heat Stable** – Stays in solution in the hottest truckmount temperatures, helping to eliminate residual deposits and clogged spray jets.
- Fibre Safe** – Safe for use on stain resist fibres. Ideal for use on all synthetic carpeting.
- Equipment Safe** – Specialty corrosion inhibitors protect your equipment components.

### Benefits Continued

- The Product of Choice** – Ultra concentrated powder formulation provides smarter cleaning at lower costs. Although suitable for truck mount use it is the ideal choice for portable users. Mixes easily in hot or warm water and is scented with a fresh fragrance.
- A Versatile Option** – Extracta Pro is ideal for use as a one step emulsifying extraction cleaner or as an extraction detergent following a prespray treatment for heavily soiled carpets.

### PRODUCT SPECIFICATIONS

**Product code:** AP457

**pH:** 9.7 - 10.0 RTU

**Fragrance:** Citrus

**Safety:** Irritant

**Colour:** Orange powder

**Substrate Suitability:** All fibre safe

**Packaging:** 4.5kg & 20kg



# Extracta Pro

High temperature extraction powder



## Directions for use:

### Dilutions:

#### Portable Extractors

- Mix 8 - 10 grams / 10Lt when cleaning wool and stain resistant carpets or where the two-step process is used.
- Mix 10 - 15 grams / 10Lt for heavy soil conditions using the single-step process.

#### Truck Mounted Extractors

- Mix 300 grams per 10Lt water to make the truck mount concentrate.
- Set the flow meter at 2 to 4 gallons per hour for cleaning wool and stain resistant carpets or where the two step process is used (prespray followed by rinse extract).
- Set the flow meter at 2 gallons per hour for stain resistant carpets.

### Application:

#### Single-step cleaning method.

(Light to medium soiling)

1. Prepare the carpet by thoroughly vacuuming the area to be cleaned.
2. Using the dilution rates specified above clean/extract the carpet or upholstery fabric using slightly overlapping strokes.
3. Apply protector if required.
4. Realign the carpet or upholstery fabric fibres and assist the drying process.

#### Application continued:

#### Two-step cleaning method.

(Medium to heavy soiling)

1. Prepare the carpet by thoroughly vacuuming the area to be cleaned and applying the relevant prespray treatment, providing the suggested dwell time and agitation.
2. Using the dilution rates specified above, rinse extract the carpet or upholstery fabric using slightly overlapping strokes.
3. Apply protector if required.
4. Realign the carpet or upholstery fabric fibres and assist the drying process.

### Notes:

Move the wand slower over areas which are more heavily soiled.

Use a dry stroke to dry the carpet faster.

